

RECEIVED
CENTRAL FAX CENTER
AUG 20 2009

CLAIM AMENDMENTS

Claim Amendment Summary

Claims pending

- Before this Amendment: Claims 1-18, 20-26, and 28-39
- After this Amendment: Claims 1-18, 20-26, and 28-39

Non-Elected, Canceled, or Withdrawn claims: None

Amended claims: None

New claims: None

Claims:

1. (Original) A method of internally controlling a clock signal of an integrated circuit device such that a data path of the integrated circuit device is initialized in a test mode, comprising the steps of:

upon a power-up condition in the test mode of the integrated circuit device forcing the clock signal of the integrated circuit device to a first logic state, thereby causing a master element of the integrated circuit device to load in first data and to conduct; and

upon completion of the power-up condition forcing the clock signal of the integrated circuit device to a second logic state, thereby latching in the first data to the master element and causing a slave element of the integrated

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-2-

circuit device to load in second data generated by the master element and to conduct.

2. (Original) The method of claim 1, wherein the first logic state is a low logic state and the second logic state is a high logic state.
3. (Original) The method of claim 1, wherein the power-up condition of the integrated circuit device is controlled by a power-on-reset signal of the integrated circuit device.
4. (Original) The method of claim 3, wherein the power-on-reset signal is an internally generated signal which changes logic state once a threshold value of a positive power supply is passed as the positive power supply rises.
5. (Original) The method of claim 1, wherein the clock signal of the integrated circuit device is an external clock signal of the integrated circuit device or a derivative signal of the external clock signal.
6. (Original) The method of claim 1, wherein the master element of the integrated circuit device is a master latch element and the slave element is a slave latch element.

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-3-

7. (Original) The method of claim 1, wherein the master element of the integrated circuit device is a master flip-flop element and the slave element is a slave flip-flop element.
8. (Original) The method of claim 1, wherein upon the power-up condition of the integrated circuit device, the clock signal is internally clocked.
9. (Original) The method of claim 1, wherein when the master element is conducting the slave element does not conduct and when the slave element is conducting the master element does not conduct.
10. (Original) The method of claim 1, wherein the test mode is entered upon the power-up condition of the integrated circuit device.
11. (Original) The method of claim 1, wherein the data path is an address path.
12. (Original) The method of claim 1, wherein in the test mode the integrated circuit device is tested at a voltage above a normal operating voltage of the integrated circuit device.
13. (Original) The method of claim 12, wherein the clock signal is tested in both the first logic state and the second logic state at the voltage.

Serial No.: 09/596,027

Atty Docket No.: 1678-026

Atty/Agent: Kevin D. Jablonski

-4-

14. (Original) The method of claim 1, wherein the integrated circuit device is a synchronous clocked device.

15. (Original) The method of claim 1, wherein conduction of the master element and conduction of the slave element initializes an address path of the integrated circuit device such that a plurality of columns and a plurality of rows of the integrated circuit device are not selected.

16. (Original) The method of claim 1, wherein conduction of the master element and conduction of the slave element initializes an address path of the integrated circuit device such that a plurality of columns and a plurality of rows of the integrated circuit device are selected.

17. (Original) The method of claim 16, wherein a plurality of bitlines true of the integrated circuit device are held at a first voltage level and a plurality of bitlines complement of the integrated circuit device are held at a second voltage level.

18. (Previously Presented) A method, comprising:
providing power to an integrated circuit;

loading a first data bit into a master latch and causing the integrated circuit to enter a test mode before the power attains a predetermined level, the master latch being disposed on the integrated circuit;

generating a second data bit from the first data bit;

latching the first data bit in the master latch; and

loading the second data bit into a slave latch that is disposed on the integrated circuit.

19. Cancel claim 19.

20. (Previously Presented) The method of claim 18 wherein generating the second data bit comprises generating the second data bit equal to the first data bit.

21. (Previously Presented) The method of claim 18 wherein generating the second data bit comprises generating the second data bit equal to a complement of the first data bit.

22. (Previously Presented) The method of claim 18 wherein generating the second data bit comprises generating the second data bit before and after the power attains the predetermined level.

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-6-

23. (Previously Presented) The method of claim 18 wherein:

loading the first data bit into the master latch comprises simulating an external

clock signal having a first clock state; and

latching the first data bit in the master latch and loading the second data bit into

the slave latch comprise simulating the external clock signal having a

second clock state.

24. (Previously Presented) The method of claim 18 wherein:

loading the first data bit into the master latch comprises simulating an external

clock signal inside the integrated circuit, the clock signal having a first

clock state; and

latching the first data bit in the master latch and loading the second data bit into

the slave latch comprise simulating the clock signal having a second clock

state.

25. (Previously Presented) A method, comprising:

generating a power-on reset signal having a first reset state when power supplied

to an integrated circuit has a predetermined first level causing the

integrated circuit to enter a test mode;

generating the power-on reset signal having a second reset state when the

power has a second predetermined level;

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-7-

loading a first data bit into a master latch of the integrated circuit in response to
the power-on reset signal having the first state;
generating a second data bit from the first data bit;
storing the first data bit in the master latch in response to the power-on reset
signal having the second state; and
loading the second data bit into a slave latch of the integrated circuit in response
to the power-on reset signal having the second state.

26. (Previously Presented) The method of claim 25 wherein:
generating the power-on reset signal having the first state comprises generating
the power-on reset signal having the first state when an integrated-circuit
supply voltage has a first predetermined voltage level; and
generating the power-on reset signal having the second state comprises
generating the power-on reset signal having the second state when the
supply voltage has a second predetermined voltage level.

27. Cancel claim 27.

28. (Previously Presented) The method of claim 25 wherein generating the
second data bit comprises generating the second data bit in response to the
power-on reset signal having either the first state or the second state.

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-8-

29. (Previously Presented) The method of claim 25 wherein storing the first data bit in the master latch and loading the second data bit into the slave latch comprise generating a test signal having a first test state.

30. (Previously Presented) The method of claim 25 wherein storing the first data bit in the master latch and loading the second data bit into the slave latch comprise generating multiple test signals each having a first test state.

31. (Previously Presented) The method of claim 25 wherein storing the first data bit in the master latch and loading the second data bit into the slave latch comprise:

generating a test signal having a test state; and

simulating an external clock signal having a clock state in response to the test signal having the test state.

32. (Previously Presented) The method of claim 25 wherein:

loading the first data bit into the master latch comprises simulating an external clock signal having a first clock state in response to the power-on reset signal having the first reset state; and

storing the first data bit in the master latch and loading the second data bit into the slave latch comprise,

generating a test signal having a test state, and

Serial No.: 09/596,027

Atty Docket No.: 1678-026

Atty/Agent: Kevin D. Jablonski

simulating the clock signal having a second clock state in response to the test signal having the test state.

33. (Previously Presented) The method of claim 25 wherein:

loading the first data bit into the master latch comprises,

simulating an external clock signal having a first clock state in response to the power-on reset signal having the first reset state,

generating a test signal having a test state, and

generating the first data bit in response to the test signal; and

storing the first data bit in the master latch and loading the second data bit into the slave latch comprise simulating the clock signal having a second clock state in response to the power-on reset signal having the second reset state and the test signal having the test state.

34. (Previously Presented) The method of claim 25 wherein:

loading the first data bit into the master latch comprises,

simulating an external clock signal having a first clock state in response to the power-on reset signal having the first reset state,

generating a test signal having a first test state, and

generating the first data bit in response to the test signal; and

storing the first data bit in the master latch and loading the second data bit into the slave latch comprise,

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-10-

generating the test signal having a second test state, and
simulating the clock signal having a second clock state in response to the
power-on reset signal having the second reset state and the test
signal having the second test state.

35. (Previously Presented) A method, comprising:
providing power to an integrated circuit;
loading a first data bit into a master latch and causing the integrated circuit to
enter a test mode before the power attains a predetermined level, the
master latch being disposed on the integrated circuit;
latching the first data bit in the master latch; and
loading the first data bit into a slave latch of the integrated circuit.
36. (Previously Presented) The method of claim 35 wherein:
loading the first data bit into the master latch comprises generating a clock signal
having a first clock state; and
latching the first data bit in the master latch and loading the first data bit into the
slave latch comprise generating the clock signal having a second clock
state.

37. (Previously Presented) The method of claim 35 wherein:

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-11-

loading the first data bit into the master latch comprises generating a clock signal inside the integrated circuit, the clock signal having a first clock state; and latching the first data bit in the master latch and loading the first data bit into the slave latch comprise generating the clock signal having a second clock state.

38. (Previously Presented) The method of claim 18 wherein:
latching the first data bit comprises latching the first data bit in the master latch after powering up the integrated circuit; and
loading the second data bit comprises loading the second data bit into the slave latch when the power attains the predetermined level.

39. (Previously Presented) The method of claim 35 wherein:
latching the first data bit comprises latching the first data bit in the master latch when the power attains the predetermined level; and
loading the first data bit into the slave latch comprises loading the first data bit into the slave latch when the power attains the predetermined level.

Serial No.: 09/596,027
Atty Docket No.: 1678-026
Atty/Agent: Kevin D. Jablonski

-12-